

HITACHI
Inspire the Next



Hitachi Building Systems Co., Ltd.

WATERRAS Tower, 2-101, Kanda Awaji-cho, Chiyoda-ku, Tokyo, 101-8941 Japan
<https://www.hitachi.com/businesses/elevator/index.html>

Contact Address:

The information in this catalogue is subject to change without notice.

Home Elevators

Luxury and convenience in your home



Japan Quality (Advanced Design)

Our home elevators developed in Japan are designed to fit into your home and villas, to add value with a wide range of advanced design.

Space-Saving

Our Machine-Room-Less design offers minimal overhead, pit depth and shaft dimension.

Single-Phase Power Supply Design

Operating on Single-phase 210-240V which is commonly available in your home and villas.

Earthquake-Resistant Design

Our home elevators complying with The Building Standard Law of Japan conform to the strength section of Japan Earthquake-Resistant standard.

User-Friendly

Our home elevators are designed to ensure the safety and comfort for all people: Providing automatic doors and multi-beam door sensors as standard on all models helps older people and people with disabilities use our home elevator more safely and comfortably.

More Comfort Atmosphere

As our home elevators apply rope type, less odors and no worry for oil leakages which may happen with hydraulic lifts.

Energy-Saving (ECO-Friendly)

The car lighting and electric fan are automatically turned off and standby power is significantly reduced (ECO Mode). In addition, LED lighting and high efficiently transformer are applied as standard.



CONTENTS

- Japan Quality (Advanced Design) — P2
- Safety — P3
- Comfort — P4
- Lineup — P5
- Glass Car Design — P7
- Deluxe Car Design — P11
- Standard Car Design — P13
- Large-Depth Car Design — P17
- Appearance — P19
- Plan View — P21
- Specifications — P22



Safety Features

Our home elevators are always provided with a wide range of safety features also found in commercial elevators.

Automatic Rescue Device for Power Failure Standard

Upon electric power supply failure, by using a rechargeable battery, a car automatically moves to the nearest lower floor (Standard) or bottom floor (Optional) and doors open for the safe evacuation of passengers.


Multi-Beam Door Sensor Standard

Multiple infrared light beams cover the door height range of 10mm to 1580mm from the floor level to detect passengers or objects. When any of the beams are blocked, the closing doors immediately reverse to re-open safely.

Modular Jack (for Landline Phone) Standard

Modular Jack is provided in the car for easy installation of a landline phone (provided by customers) that enables passengers to notify or communicate directly with outside.

*It is highly recommended to provide the landline phone in the car to call for help in case of emergency.
*Instead of providing the landline phone, a mobile phone can be kept in the car all the time because USB Power Supply enables the mobile phone to be charged.
*Make sure that outside call over the landline phone or mobile phone is working in advance.



Comfort features

Our home elevators offer a wide range of comfort features for your home and villas.

Extending Door Opening Time Standard

Door opening time can be extended by 3 minutes by pressing Door Open Button on Car Operating Panel or Hall Call Button while the doors are open.

USB Power Supply (Type-A/DC5V 2.4A) Standard

USB charging port can be used for various purposes (such as fan, aroma diffuser and air cleaners provided by Customers)



Management Key Switch Standard

Management Key Switch installed at bottom floor deactivates the elevator.

For example, owner can take the elevator out of service manually with this switch before leaving the house to prevent children from playing with the elevator.



One Additional Management Key Switch Optional

One Additional Management Key Switch can be applied at any floor other than bottom floor.

For example, if Management Key Switch is applied at ground floor (main entrance) and basement floor (garage), owner can more conveniently switch to disable/able the elevator.

[Access Here for Home Elevators Promotion Movie](#)



Specifications are subject to change without notice.
Actual color may differ slightly from those shown.

Lineup

	Glass Car Design		Deluxe Car Design		Standard Car Design			Large-Depth Car Design	
	SVC260G	SHA240G	SVC260D	SVC200D	SHA300S	SVC280S	SVC200S	SVC260SL	
Rated Capacity	260Kg	240kg	260kg	200kg	300kg	280kg	200kg	260kg	
Persons	4	3	4	3	4	4	3	4	
Door Type	4-Panel Center Opening	2-Panel Center Opening	4-Panel Center Opening		2-Panel Center Opening	4-Panel Center Opening		4-Panel Center Opening	
Car	 	 	 	 	 	 	 		
Rated Speed	Up 20m/min, Down 30m/min				Up 20m/min, Down 30m/min				
Max. Stops	5				5				
Max. Travel (m)	 1-Gate	13				13			
	 2-Gate	-		10	-		10	-	
Car Size (mm)	(W)950 x (D)1150 x (H)2100		(W)950 x (D)1150 x (H)2000*1		(W)950 x (D)1150 x (H)2000*1			(W)880 x (D)1300 x (H)2000*1	
Door Opening Size (mm)	(W)800 x (H)2000		(W)800 x (H)1900*2		(W)800 x (H)1900*2				

*1 Optional: (H)2100mm *2 Optional: (H)2000mm
Please see page 21 for more details

Specifications are subject to change without notice.
Actual color may differ slightly from those shown.

Glass Car Design (For Indoor / Outdoor Enclosed)

Access Here for Design Simulator
Design Simulator enables to visualize the car and entrance design.




Car Design

SVC260G
4 Persons / 260Kg



- Ceiling** — LED Down Light Type: SUS-HL
- Side Walls, Front Return & Transom Panel** — SUS-HL
- Car Doors** — SUS-HL
- Windows** — Triple Slit Transparent Glass (Optional)
- Floor** — F-33(Optional)
- Handrail** — Rear side Handrail (Stainless Steel)
- Telephone** — Provided by Customers



Entrance Design



- Entrance Doors / Frame** — SUS-HL (Optional)
- Windows** — Triple slit Transparent Glass (Optional)


Entrance Doors / Entrance Door Frame



Basic Specifications

		SVC260G
Rated Capacity		4 Persons / 260kg
Rated Speed		Up 20m/min, Down 30m/min
Max. Stops		5
Max. Travel	1-Gate	13m
	2-Gate	-
Driving System		Basement Drum Type
Control System		VVVF Inverter Drive
Power Supply		Single-Phase 210V•220V•230V•240V 2-Wired
Door Type		4-Panel Center Opening
Starting Frequency		150 times/day

Floor



*The pattern is different individually due to the natural stone.

Specifications are subject to change without notice. Actual color may differ slightly from those shown.

Glass Car Design (For Indoor / Outdoor Enclosed)

Access Here for Design Simulator
Design Simulator enables to visualize the car and entrance design.



Car Design

SHA240G
3 Persons / 240Kg



- Ceiling** — LED Down Light
Type: SUS-HL
- Side Walls, Front Return & Transom Panel** — SUS-HL
- Car Doors** — SUS-HL
- Windows** — Large Transparent Glass (Optional)
- Floor** — F-32 (Optional)
- Handrail** — 3 side Handrails (Stainless Steel)
- Telephone** — Provided by Customers

Ceiling Type
LED Down Light Type (CE-VCB-C30)
Stainless Steel Plate Hairline



Diffuser
(Electric Fan: Optional)

Walls
Stainless Steel Plate Hairline

Front Return Panel
Stainless Steel Plate Hairline

Transom Panel
Stainless Steel Plate Hairline



Car Doors
Stainless Steel Plate Hairline


3 side Handrails
Stainless Steel

Floor


[Natural Marble*] Optional



Bianco White (F-31)



Nero Black (F-32)



Tutto White (F-33)

[Wood] Optional



Casual Oak (F-7)

[Vinyl Floor Tile]



Ajax Soft (F-24)



Calacatta Gold (F-25)



Natural Cherry (F-16)



Dark Brown Oak (F-17)



Light Brown (F-11)



Gray (F-12)

*The pattern is different individually due to the natural stone.

Specifications are subject to change without notice.
Actual color may differ slightly from those shown.

Basic Specifications

		SHA240G
Rated Capacity		3 Persons / 240kg
Rated Speed		Up 20m/min, Down 30m/min
Max. Stops		5
Max. Travel	1-Gate	13m
	2-Gate	-
Driving System		Basement Drum Type
Control System		VVVF Inverter Drive
Power Supply		Single-Phase 210V•220V•230V•240V 2-Wired
Door Type		2-Panel Center Opening
Starting Frequency		150 times/day

Entrance Design



Entrance Doors / Frame — SUS-HL (Optional)

Windows — Large Transparent Glass (Optional)

Entrance Doors / Entrance Door Frame

[Stainless Steel Plate] Optional



Hairline (SUS-HL)



Hairline Titan Gold (MG-GH1)



Etching (MD-102)



Etching (MD-143)

[Coated Steel Plate] Standard



Urban Black Mahogany (MS90)



Dark Mahogany (MS91)



Solid Black (MS132)




Camel Walnut (MS93)



Gilfy Ash (MS134)



Cream Feather (MS135)



Snow Willow (MS96)



Ice White (MS138)

Deluxe Car Design

Access Here for Design Simulator
Design Simulator enables to visualize
the car and entrance design.



Car Design



SVC260D
4 Persons / 260kg



SVC200D
3 Persons / 200kg



Car Design Example



- Ceiling** — LED Full Ceiling Light Type
- Stainless Mirror** — MR-VCB-NN0-SN
- Rear Wall** — MS138
- Side Walls** — MS138
- Bottom Wall of Car Operating Panel** — MS138
- Floor** — F-31 (Optional)
- Handrail (Optional)** — Black Wood
- Telephone** — Provided by Customers



- Ceiling** — LED Down Light Type: MS96
- Stainless Mirror** — MR-VCB-NN0-ST (Optional)
- Rear Wall** — MS96
- Side Walls** — MS90
- Bottom Wall of Car Operating Panel** — MS90
- Floor** — F-32 (Optional)
- Handrail (Optional)** — Black Wood
- Telephone** — Provided by Customers

- Ceiling** — LED Full Ceiling Light Type
- Stainless Mirror** — MR-VCB-NN0-ST (Optional)
- Side Walls** — MS96
- Bottom Wall of Car Operating Panel** — MS90
- Front Return & Transom Panel** — MS96
- Car Doors** — MS96
- Windows** — Double Slit Gray Smoked Plastic
- Floor** — F-31 (Optional)
- Handrail (Optional)** — Black Wood
- Telephone** — Provided by Customers

Basic Specifications

	SVC260D	SVC200D
Rated Capacity	4 Persons / 260kg	3 Persons / 200kg
Rated Speed	Up 20m/min, Down 30m/min	
Max. Stops	5	
Max. Travel	1-Gate	13m
	2-Gate	10m
Driving System	Basement Drum Type	
Control System	VVVF Inverter Drive	
Power Supply	Single-Phase 210V•220V•230V•240V 2-Wired	
Door Type	4-Panel Center Opening	
Starting Frequency	150 times/day	

Entrance Design



- Entrance Doors / Frame** — MS135
- Windows** — Double Slit Transparent Glass (Optional)

Ceiling / Rear Wall / Side Walls / Bottom Wall of Car Operating Panel / Front Return & Transom Panel

- [Coated Steel Plate]** **Standard**
- Urban Black Mahogany (MS90)
 - Cream Feather (MS135)
 - Snow Willow (MS96)
 - Ice White (MS138)

Stainless Mirror

- Optional**
- Stainless Mirror Titan Bronze (MR-VCB-NN0-ST)
- Standard**
- Stainless Mirror (MR-VCB-NN0-SN)

Diffuser
(Electric Fan: Standard)

Handrail (Optional)
→ P20

Front Return Panel
Transom Panel

Car Doors / Entrance Doors / Entrance Door Frame

- [Stainless Steel Plate]** **Optional**
- Hairline (SUS-HL)
 - Hairline Titan Gold (MG-GH1)
 - Etching (MD-102)
 - Etching (MD-143)
- [Coated Steel Plate]** **Standard**
- Urban Black Mahogany (MS90)
 - Dark Mahogany (MS91)
 - Solid Black (MS132)
 - Camel Walnut (MS93)
 - Gilfy Ash (MS134)
 - Cream Feather (MS135)
 - Snow Willow (MS96)
 - Ice White (MS138)

Ceiling Type

- LED Full Ceiling Light Type (CE-VCB-D30)
- LED Down Light Type (CE-VCB-C30)
- LED Square Cover Light Type (CE-VCB-E30)

Floor

- [Natural Marble*]** **Optional**
- Bianco White (F-31)
 - Nero Black (F-32)
 - Tutto White (F-33)
- [Wood]** **Optional**
- Casual Oak (F-7)
- [Vinyl Floor Tile]**
- Ajax Soft (F-24) **Optional**
 - Calacatta Gold (F-25) **Optional**
 - Natural Cherry (F-16) **Standard**
 - Dark Brown Oak (F-17) **Standard**
- [Carpet]** **Standard**
- Calm Black (F-21)
 - Ebony Brown (F-22)

*The pattern is different individually due to the natural stone. Not applicable to 2-Gate Model.

Specifications are subject to change without notice.
Actual color may differ slightly from those shown.

Standard Car Design

Car Design

Access Here for Design Simulator
Design Simulator enables to visualize
the car and entrance design.



SHA300S
4 Persons / 300kg



- Ceiling** — LED Down Light Type: MS96
- Side Walls, Front Return & Transom Panel** — MS96
- Car Doors** — MS96
- Windows** — Large Transparent Glass (Optional)
- Floor** — F-31 (Optional)
- Handrail (Optional)** — Black Wood
- Telephone** — Provided by Customers

Basic Specifications

		SHA300S
Rated Capacity		4 Persons / 300kg
Rated Speed		Up 20m/min, Down 30m/min
Max. Stops		5
Max. Travel	1-Gate	13m
	2-Gate	-
Driving System		Basement Drum Type
Control System		VVVF Inverter Drive
Power Supply		Single-Phase 210V•220V•230V•240V 2-Wired
Door Type		2-Panel Center Opening
Starting Frequency		150 times/day

Car Design Example



- Ceiling** — LED Down Light Type: SUS-HL (Optional)
- Rear Wall** — MR-VCB-NN0-SN (Optional)
- Side Walls** — SUS-HL (Optional)
- Floor** — F-12
- Handrail (Optional)** — Stainless Steel
- Telephone** — Provided by Customers



- Ceiling** — LED Rectangle Cover Light Type: MS135
- Rear Wall** — MS135
- Side Walls** — MS135
- Floor** — F-17
- Handrail (Optional)** — Black Wood
- Mirror (Optional)** — Aluminium Frame
- Telephone** — Provided by Customers

Entrance Design



- Entrance Doors / Frame** — SUS-HL (Optional)
- Windows** — Large Transparent Glass (Optional)

Ceiling / Rear Wall / Side Walls, Front Return & Transom Panel

[Stainless Steel Plate] Optional

Hairline (SUS-HL)

[Coated Steel Plate] Standard

Urban Black Mahogany (MS90) Cream Feather (MS135) Snow Willow (MS96) Ice White (MS138)

[Stainless Mirror] (Rear Wall only) Optional

Stainless Mirror (MR-VCB-NN0-SN) Stainless Mirror Titan Gold (MR-VCB-NN0-SG)



Car Doors / Entrance Doors / Entrance Door Frame

[Stainless Steel Plate] Optional

Hairline (SUS-HL) Hairline Titan Gold (MG-GH1) Etching (MD-102) Etching (MD-143)

[Coated Steel Plate] Standard

Urban Black Mahogany (MS90) Dark Mahogany (MS91) Solid Black (MS132) Camel Walnut (MS93)

Gilfy Ash (MS134) Cream Feather (MS135) Snow Willow (MS96) Ice White (MS138)

Ceiling Type



LED Down Light Type (CE-VCB-C30)



LED Rectangle Cover Light Type (CE-VCB-A30)


Diffuser (Electric Fan: Optional)

Floor

[Natural Marble*] Optional



Bianco White (F-31)



Nero Black (F-32)



Tutto White (F-33)

[Wood] Optional



Casual Oak (F-7)

[Vinyl Floor Tile]



Ajax Soft (F-24)



Calacatta Gold (F-25)



Natural Cherry (F-16)



Dark Brown Oak (F-17)

[Carpet] Standard



Light Brown (F-11)



Gray (F-12)

*The pattern is different individually due to the natural stone.

Specifications are subject to change without notice. Actual color may differ slightly from those shown.

Standard Car Design

Access Here for Design Simulator
Design Simulator enables to visualize
the car and entrance design.



Car Design



SVC280S
4 Persons / 280kg



SVC200S
3 Persons / 200kg



Car Design Example



- Ceiling** — LED Down Light Type: MS96
- Rear Wall** — MS96
- Side Walls** — MS96
- Floor** — F-24 (Optional)
- Handrail (Optional)** — Stainless Steel
- Mirror (Optional)** — Aluminium Frame
- Telephone** — Provided by Customers



- Ceiling** — LED Rectangle Cover Light Type: MS138
- Rear Wall** — MR-VCB-NN0-SG (Optional)
- Side Walls** — MS90
- Floor** — F-31 (Optional)
- Handrail (Optional)** — Black Wood
- Telephone** — Provided by Customers

- Ceiling** — LED Down Light Type: SUS-HL (Optional)
- Side Walls, Front Return & Transom Panel** — SUS-HL (Optional)
- Car Doors** — SUS-HL (Optional)
- Windows** — Double Slit Gray Smoked Plastic
- Floor** — F-32 (Optional)
- Handrail (Optional)** — Stainless Steel
- Telephone** — Provided by Customers

Basic Specifications

	SVC280S	SVC200S
Rated Capacity	4 Persons / 280kg	3 Persons / 200kg
Rated Speed	Up 20m/min, Down 30m/min	
Max. Stops	5	
Max. Travel	1-Gate	13m
	2-Gate	10m
Driving System	Basement Drum Type	
Control System	VVVF Inverter Drive	
Power Supply	Single-Phase 210V•220V•230V•240V 2-Wired	
Door Type	4-Panel Center Opening	
Starting Frequency	150 times/day	

Entrance Design



- Entrance Doors / Frame** — MS134
- Windows** — Double Slit Transparent Glass (Optional)

Ceiling / Rear Wall / Side Walls, Front Return & Transom Panel

[Stainless Steel Plate] Optional

Hairline (SUS-HL)

[Coated Steel Plate] Standard

Urban Black Mahogany (MS90) Cream Feather (MS135) Snow Willow (MS96) Ice White (MS138)

[Stainless Mirror] (Rear Wall only) Optional

Stainless Mirror (MR-VCB-NN0-SN) Stainless Mirror Titan Gold (MR-VCB-NN0-SG)



Car Doors / Entrance Doors / Entrance Door Frame

[Stainless Steel Plate] Optional

Hairline (SUS-HL) Hairline Titan Gold (MG-GH1) Etching (MD-102) Etching (MD-143)

[Coated Steel Plate] Standard

Urban Black Mahogany (MS90) Dark Mahogany (MS91) Solid Black (MS132) Camel Walnut (MS93)

Gilfy Ash (MS134) Cream Feather (MS135) Snow Willow (MS96) Ice White (MS138)

Ceiling Type



LED Down Light Type (CE-VCB-C30)



LED Rectangle Cover Light Type (CE-VCB-A30)


Diffuser (Electric Fan: Optional)

Floor

[Natural Marble*] Optional



Bianco White (F-31)



Nero Black (F-32)



Tutto White (F-33)

[Wood] Optional



Casual Oak (F-7)

[Vinyl Floor Tile]




Ajax Soft (F-24)

[Optional]




Calacatta Gold (F-25)

[Optional]



Natural Cherry (F-16)

[Standard]



Dark Brown Oak (F-17)

[Standard]



Light Brown (F-11)

[Standard]



Gray (F-12)

*The pattern is different individually due to the natural stone. Not applicable to 2-Gate Model.

Specifications are subject to change without notice. Actual color may differ slightly from those shown.

Large-Depth Car Design

Car Design

Access Here for Design Simulator
Design Simulator enables to visualize
the car and entrance design.



SVC260SL
4 Persons / 260kg



Large-Depth Type

- Ceiling** — LED Rectangle Cover Light Type: MS138
- Side Walls, Front Return & Transom Panel** — MS138
- Car Doors** — MS138
- Windows** — Double Slit Gray Smoked Plastic
- Floor** — F-12
- Handrail (Optional)** — Black Wood
- Telephone** — Provided by Customers

Basic Specifications

		SVC260SL
Rated Capacity		4 Persons / 260kg
Rated Speed		Up 20m/min, Down 30m/min
Max. Stops		5
Max. Travel	1-Gate	13m
	2-Gate	-
Driving System		Basement Drum Type
Control System		VVVF Inverter Drive
Power Supply		Single-Phase 210V•220V•230V•240V 2-Wired
Door Type		4-Panel Center Opening
Starting Frequency		150 times/day

Car Design Example



- Ceiling** — LED Down Light Type: MS90
- Rear Wall** — MS90
- Side Walls** — MS90
- Floor** — F-7 (Optional)
- Handrail (Optional)** — Beige Wood
- Mirror (Optional)** — Aluminium Frame
- Telephone** — Provided by Customers



- Ceiling** — LED Rectangle Cover Light Type: MS135
- Rear Wall** — MR-VCB-NN0-SN (Optional)
- Side Walls** — MS135
- Floor** — F-11
- Handrail (Optional)** — Stainless Steel
- Telephone** — Provided by Customers

Entrance Design



- Entrance Doors / Frame** — MS91
- Windows** — Triple Slit Transparent Glass (Optional)

Ceiling / Rear Wall / Side Walls, Front Return & Transom Panel

[Stainless Steel Plate] Optional

Hairline (SUS-HL)


[Coated Steel Plate] Standard

Urban Black Mahogany (MS90) Cream Feather (MS135) Snow Willow (MS96) Ice White (MS138)

[Stainless Mirror] (Rear Wall only) Optional

Stainless Mirror (MR-VCB-NN0-SN) Stainless Mirror Titan Gold (MR-VCB-NN0-SG)

Ceiling Type



Car Doors / Entrance Doors / Entrance Door Frame

[Stainless Steel Plate] Optional

Hairline (SUS-HL) Hairline Titan Gold (MG-GH1) Etching (MD-102) Etching (MD-143)

[Coated Steel Plate] Standard

Urban Black Mahogany (MS90) Dark Mahogany (MS91) Solid Black (MS132) Camel Walnut (MS93)

Gilfy Ash (MS134) Cream Feather (MS135) Snow Willow (MS96) Ice White (MS138)

Floor

[Wood] Optional

Casual Oak (F-7)

[Vinyl Floor Tile]

Ajax Soft (F-24) Optional

Calacatta Gold (F-25) Optional

Natural Cherry (F-16) Standard

Dark Brown Oak (F-17) Standard

[Carpet] Standard

Light Brown (F-11)

Gray (F-12)

* Natural Marble is not applicable to SVC260SL.

Specifications are subject to change without notice.
Actual color may differ slightly from those shown.

Appearances

Car and Entrance Door Windows

2-Panel Center Opening Door (SHA240G/SHA300S)

[Window Type]

Large Transparent Glass Optional

No Window Standard



4-Panel Center Opening Door (SVC260G/SVC260D/SVC200D/SVC280S/SVC200S/SVC260SL)

[Window Shape]

Triple Slit* Optional

Double Slit Standard

No Window Standard



*When 100mm Higher Car Ceiling Height & Entrance Height is applied, Triple Slit is applied as standard.
*Triple slit is applied as standard for SVC260G

[Window Material]

Transparent Glass Optional

Gray Smoked Plastic Standard



Handrails Optional



Beige Wood (HR-RJ0-S30W)



Black Wood (HR-RJ0-S30B)



Stainless Steel (HR-EB0-S30S)

Mirrors Optional



Aluminium Frame (MR-ED0-ANO-LGN)

Car Wall Protect Plate Optional



Signalization


Car Operating Panel Standard



Door Open Button


Emergency Bell Button

Message Lamp



*This lamp lights up only when Earthquake Emergency Operation with P-Wave Sensor (Optional) is applied.

Hall Call Button Standard



ECO Mode Lamp


Hall Call Register Lamp

Operation Lamp

Call Button


Plan View

Shaft Plan



Elevation Plan

[All Models]



Item	Glass Car Design		Deluxe Car Design		Standard Car Design			Large-Depth Car Design
	SVC260G	SHA240G	SVC260D	SVC200D	SHA300S	SVC280S	SVC200S	SVC260SL
(A) Car ceiling height	2100		2000/2100 (*)					
(B) Entrance height	2000		1900/2000 (*)					
(C) Min. Overhead dimension	2500		2450/2550 (*)		2400/2500 (*)			
(D) Max. Travel	1Gate Model	13000						
	2Gate Model	-	-	10000	-	-	10000	-
(E) Min. PIT	1Gate Model	560/610 (**)						
	2Gate Model	-	-	760/800 (**)	-	-	760/800 (**)	-

*1 When 100mm Higher Car Ceiling Height & Entrance Height (Optional) is applied
 **2 When Double Isolation Unit for Absorbing Vibration and Sound (Optional) is applied

Specifications

Item	Glass Car Design		Deluxe Car Design		Standard Car Design			Large-Depth Car Design
	SVC260G	SHA240G	SVC260D	SVC200D	SHA300S	SVC280S	SVC200S	SVC260SL
Safety Feature	Multi-Beam Door Sensor (MBDS)	●	●	●	●	●	●	●
	Overload Return Door System (ORS)	●	●	●	●	●	●	●
	Nearest Landing operation for Minor Trouble (NLNO)	●	●	●	●	●	●	●
	Next Drive Operation (NXTD)	●	●	●	●	●	●	●
	Overload Detection System (OLDS)	●	●	●	●	●	●	●
	Automatic Rescue Device for Power Failure (ARD) Landing on Nearest Lower Floor	●	●	●	●	●	●	●
	Automatic Rescue Device for Power Failure (ARD) Landing on Bottom Floor	○	○	○	○	○	○	○
	Car Emergency Lighting (CEML)	●	●	●	●	●	●	●
	Emergency Bell Button	●	●	●	●	●	●	●
	Unintended Car Movement Protection System	●	●	●	●	●	●	●
Energy-Saving	ECO Mode	●	●	●	●	●	●	●
Car Design	Handrail (Wood / Stainless Steel)	● ^{*4}	● ^{*5}	○	○	○	○	○
	Mirror (Aluminium Frame)	-	-	-	-	○	○	○
	Electric Fan	○	○	●	●	○	○	○
	Car Wall Protect Plate	○	○	-	-	○	○	○
	Stainless Steel Plate (Ceiling / Wall / Front Return & Transom Panel)	●	●	-	-	○	○	○
	Stainless Steel Plate (Car Doors)	●	●	○	○	○	○	○
	Stainless Mirror (at Whole Rear Wall)	-	-	-	-	○	○	○
Floor	Stainless Mirror Titan Gold (at Whole Rear Wall)	-	-	-	-	○	○	○
	Stainless Mirror (at Center Panel of Rear Wall & at Panel above Car Operating Panel)	-	-	●	●	-	-	-
	Stainless Mirror Titan Bronze (at Center Panel of Rear Wall & at Panel above Car Operating Panel)	-	-	○	○	-	-	-
	Carpet (F-11, F-12)	●	●	-	-	●	●	●
	Carpet (F-21, F-22)	-	-	●	●	-	-	-
Comfort	Vinyl Floor Tile (F-16, F-17)	●	●	●	●	●	●	●
	Vinyl Floor Tile (F-24, F-25) / Wood	○	○	○	○	○	○	○
	Natural Marble (F-31, F-32, F-33) ^{*1}	○	○	○	○	○	○	-
Car & Entrance Door Windows	2-Gate Model (Only one side opening at each floor)	-	-	-	○	-	-	-
	100mm Higher Car Ceiling Height and Entrance Height	●	●	○	○	○	○	○
	No Window	● ^{*4}	●	●	●	●	●	●
	Large Transparent Glass Windows	-	○	-	-	○	-	-
Entrance Design	Double Slit Plastic Windows	-	-	●	●	-	●	●
	Double Slit Transparent Glass Windows	-	-	○	○	-	○	○
	Triple Slit Plastic Windows ^{*2}	●	-	○	○	-	○	○
	Triple Slit Transparent Glass Windows	○	-	○	○	-	○	○
Function	Stainless Steel Plate	○	○	○	○	○	○	○
	Message Lamp (on Car Operating Panel)	●	●	●	●	●	●	●
	Modular Jack / USB Power Supply	●	●	●	●	●	●	●
	Extending Door Opening Time (3 Minutes)	●	●	●	●	●	●	●
	Management Key Switch (Bottom Floor)	●	●	●	●	●	●	●
	One Additional Management Key Switch	○	○	○	○	○	○	○
	Double Isolation Unit for Absorbing Vibration and Sound ^{*3}	○	○	○	○	○	○	○
	Earthquake Emergency Operation (EEMO) with P-Wave Sensor	○	○	○	○ ^{*6}	○	○	○ ^{*6}
	Fire Emergency Operation (FEMO)	○	○	○	○	○	○	○
	Flood Emergency Operation	○	○	○	○	○	○	○
	Car Indicator	○	○	○	○ ^{*6}	○	○	○ ^{*6}
	Hall Position Indicator	○	○	○	○	○	○	○
Car Arrival Chime	○	○	○	○	○	○	○	
Bleep Button	○	○	○	○	○	○	○	

*1 Not applicable to 2-Gate Model.
 *2 When 100mm Higher Car Ceiling Height and Entrance Height (Optional) is applied, Triple Slit Plastic Windows are applied as standard.
 *3 Shall be applied for Maisonette residence.
 *4 Rear side handrail (Stainless Steel) is Standard.
 *5 3 side handrails (Stainless Steel) is Standard
 *6 Required by Building Standard Law of Japan when travel is over 7m.

NOTE1 No fuse breaker for home elevator shall be inverter compatible model supplied by others.
 NOTE2 Applicable standard: Building Standard Law of Japan for SVC200D, SVC200S
 Manufacturer's Standard for SVC260G, SHA240G, SVC260D, SHA300S, SVC280S, SVC260SL

Specifications are subject to change without notice.
 Actual color may differ slightly from those shown.